



VS-41H

This is a high performance HDMI 4x1 switcher that supports HDTV formats up to 4Kx2K@60Hz. and all HDMI 3D TV formats. it can extract HDMI stream audio to separate digital and analog audio output. This product supports HDCP repeater/CEC/ARC functions. Select any of the inputs by front panel button or IR remote, the corresponding indicator LED on the front panel will be illuminated.

FEATURE

- Compliant with HDMI 2.0a, DVI 1.0 standards.
- HDCP 2.2 and HDCP 1.4 compliant
- Video formats up to 4Kx2K@60 and all HDMI 3D video formats.
- Support PCM, Dolby TrueHD, DTS-HD Master Audio up to 7.1CH
- Digital and analog audio output
- Support smart EDID management (Audio/2CH/5.1CH/7.1CH selectable)
- Support input port auto switching or manual switching mode
- Audio Return Channel (ARC) support

SPECIFICATION

Technical

Frequency Bandwidth:	18Gbps.
Input Ports:	4x HDMI Female port 1x IR Receive port 1x RS-232 port
Output Port:	1x HDMI Female port
HDMI Audio Output:	PCM2.1/5.1/7.1CH, Dolby 5.1, DTS5.1, Dolby-TrueHD, DTS-HD
ESD Protection:	Human body model — ±8kV (air-gap discharge) & ±4kV (contact discharge)
Dimensions:	85mm (W) x 180mm (D) x 11.6mm (H)
Weight:	300g.
Power Supply:	Input: AC100-240V 50/60Hz Output: DC 24V/2.7A (US/EU standards, CE/FCC/UL certified)
Power Consumption:	2.5W (Max)
Operation Temperature:	14°F - 122°F / -10°C - 50°C
Storage temperature:	-4°F - 140°F / -20°C - 60°C

